



ROLLER



PANEL



ROMAN



VERTICAL
(BLOCKOUT ONLY)

Technical Data

Composition	100% Polyester
Width	Blockout: 3,000mm, 127mm & 89mm Light Filtering: 3,000mm
Weight	Blockout 390gsm +/-5% Light filtering 220gsm +/-5%
Thickness	Blockout 0.60mm +/-5% Light filtering 0.55mm +/-5%
Opacity/Openness	Blockout tested to AS-2663-1999
Light Fastness	≥ 5 (Blue wool scale)
Coating	Blockout coated with acrylic foam Light filtering stiffened with acrylic
Flame Retardant	Product is designed and manufactured to comply with Building Code of Australia requirements for class 2 to 9 buildings
Cleaning	Surface dust can be removed with vacuum or a soft cloth



5 YEAR
WARRANTY



BLOCKOUT



LIGHT
FILTERING



ECO
FRIENDLY



PVC FREE



Solar Properties

	European standard tested to DIN EN 410: 2011				Tested to EN 14501			
	Ts	Rs	As	Tv/ Vlt	Tuv	O-F	Single Glass Reference Glazing A [g window 0.85] [U window 5.7] g-total	High Performance Glass Reference Glazing D [g window 0.32] [U window 1.1] g-total
Blockout	0	83	17	0	0	0	0.23	0.23
White LF	46	54	0	47	33	4	0.46	0.26
Dove LF	25	34	41	21	15	3	0.55	0.28
Concrete LF	37	42	21	34	24	4	0.52	0.27
Pearl LF	46	53	1	47	34	4	0.47	0.27
Birch LF	40	48	12	39	27	3	0.49	0.27
Puffy LF	40	48	12	39	28	5	0.49	0.27
Pyrite LF	17	21	62	15	11	4	0.61	0.29
Bourneville LF	10	11	79	9	8	5	0.66	0.30
Steel LF	13	17	70	11	9	4	0.63	0.29
Jet LF	7	8	85	6	5	4	0.68	0.30

Ts Solar Transmittance

As Solar Absorbance

G-Value % Solar Radiation through Fabric

Rs Solar Reflection

Tv Visual Light Transmission

G-Total % Solar Radiation through Blind and Window

Melbourne Head Office

Building 1, Level 2, 630 Mitcham Road
Mitcham VIC 3132 Australia

P +61 3 9729 9970
E sales@texstyle.com.au

Learn more at
texstyle.com.au

